

Package: aLBI (via r-universe)

August 25, 2024

Type Package

Title Estimating Length-Based Indicators for Fish Stock

Version 0.1.5

Maintainer Ataher Ali <ataher.cu.ms@gmail.com>

Description Provides tools for estimating length-based indicators from length frequency data to assess fish stock status and manage fisheries sustainably. Implements methods from Cope and Punt (2009) <[doi:10.1577/C08-025.1](https://doi.org/10.1577/C08-025.1)> for data-limited stock assessment and Froese (2004) <[doi:10.1111/j.1467-2979.2004.00144.x](https://doi.org/10.1111/j.1467-2979.2004.00144.x)> for detecting overfishing using simple indicators. Key functions include: CalPar(): Calculates various lengths used in fish stock assessment as biological length indicators such as asymptotic length (Linf), maximum length (Lmax), length at sexual maturity (Lm), and optimal length (Lopt). FishPar(): Calculates length-based indicators (LBIs) proposed by Froese (2004) <[doi:10.1111/j.1467-2979.2004.00144.x](https://doi.org/10.1111/j.1467-2979.2004.00144.x)> such as the percentage of mature fish (Pmat), percentage of optimal length fish (Popt), percentage of mega spawners (Pmega), and the sum of these as Pobj. This function also estimates confidence intervals for different lengths, visualizes length frequency distributions, and provides data frames containing calculated values. FishSS(): Makes decisions based on input from Cope and Punt (2009) <[doi:10.1577/C08-025.1](https://doi.org/10.1577/C08-025.1)> and parameters calculated by FishPar() (e.g., Pobj, Pmat, Popt, LM_ratio) to determine stock status as target spawning biomass (TSB40) and limit spawning biomass (LSB25). These tools support fisheries management decisions by providing robust, data-driven insights.

Depends R (>= 3.5.0)

Suggests testthat, knitr, rmarkdown, devtools, readxl

License GPL-3

Encoding UTF-8

LazyData true

URL <https://github.com/Ataher76/aLBI>
BugReports <https://github.com/Ataher76/aLBI/issues>
RoxygenNote 7.3.1
VignetteBuilder knitr
Repository <https://ataher76.r-universe.dev>
RemoteUrl <https://github.com/ataher76/albi>
RemoteRef HEAD
RemoteSha 4c66973637079f06b38ebad77d986cf93113029c

Contents

CPdata	2
FishPar	3
FishSS	4
lenfreq01	4
lenfreq02	5

Index	6
--------------	----------

CPdata	<i>CPdata: Example dataset for aLBI package</i>
--------	---

Description

This dataset contains description of CPdata.

Usage

```
data(CPdata)
```

Format

A data frame with [number of rows] rows and 11 columns:

- A [description of column A]
- B [description of column B]
- C [description of column C]
- D [description of column D]
- E [description of column E]
- F [description of column F]
- G [description of column G]
- H [description of column H]
- I [description of column I]
- J [description of column J]
- Tx [description of column Tx]

Source

[Include the source of the data if available]

Examples

```
data(CPdata)
head(CPdata)
```

FishPar

Calculate Length-Based Indicators for Fish Stock Assessment #'@importFrom graphics abline axis barplot box boxplot hist legend lines par rect segments text

Description

This function calculates various length-based indicators for fish stock assessment using length frequency data and bootstrap resampling.

Usage

```
FishPar(data, resample, progress)
```

Arguments

- | | |
|-----------------------|--|
| <code>data</code> | A data frame containing two columns: Length and Frequency. |
| <code>resample</code> | An integer indicating the number of bootstrap resamples. |
| <code>progress</code> | A logical value indicating whether to display progress. |

Value

A list containing estimated length parameters, Froese indicators, and other relevant metrics.

Examples

```
data <- data.frame(Length = c(10, 20, 30, 40, 50), Frequency = c(5, 10, 15, 20, 25))
FishPar(lenfreq01, 100, progress = FALSE)
utils::data("lenfreq01", package = "aLBI")
utils::data("lenfreq02", package = "aLBI")
```

FishSS*Assess Stock Status Based on Calculated Parameters***Description**

This function assesses the stock status based on parameters calculated by the FishPar function.

Usage

```
FishSS(data, LM_ratio, Pobj, Pmat, Popt)
```

Arguments

<code>data</code>	A data frame containing the necessary columns for stock status calculation.
<code>LM_ratio</code>	A numeric value representing the length at maturity ratio.
<code>Pobj</code>	A numeric value representing the percentage objective.
<code>Pmat</code>	A numeric value representing the percentage of mature fish.
<code>Popt</code>	A numeric value representing the percentage of optimally sized fish.

Value

A numeric vector containing TSB40 and LSB25.

Examples

```
utils::data("CPdata", package = "aLBI")
FishSS(CPdata, 0.75, 100, 30, 25)
```

lenfreq01*lenfreq01: Example dataset for aLBI package***Description**

This dataset contains description of lenfreq01.

Usage

```
data(lenfreq01)
```

Format

A data frame with [number of rows] rows and 2 columns:

Frequency [description of column Frequency]

Length [description of column Length]

Source

[Include the source of the data if available]

Examples

```
data(lenfreq01)
head(lenfreq01)
```

lenfreq02

lenfreq02: Example dataset for aLBI package

Description

This dataset contains description of lenfreq02.

Usage

```
data(lenfreq02)
```

Format

A data frame with [number of rows] rows and 2 columns:

Frequency [description of column Frequency]
LengthClass [description of column LengthClass]

Source

[Include the source of the data if available]

Examples

```
data(lenfreq02)
head(lenfreq02)
```

Index

CPdata, [2](#)

FishPar, [3](#)

FishSS, [4](#)

lenfreq01, [4](#)

lenfreq02, [5](#)